



Exceptional Mammography Imaging for Quality Diagnoses

The precision and reliability you expect from DRYVIEW Laser Imaging Film is also available in mammography-quality film. DRYVIEW DVM and DVM+ Mammography Laser Imaging Films feature precise, high-quality imaging and superior maximum densities that are preferred for mammography imaging. (Dmax \geq 4.0 when using DVM+ film).

DRYVIEW Mammography Laser Imaging Films produce images with a wide dynamic range and a distinct black tone, which ensures highly consistent image contrast. Exceptional mammography images empower you and your staff to make confident diagnoses and provide extraordinary patient care.



ADVANTAGES AT A GLANCE

- Variety of film sizes—DRYVIEW DVM and DVM+ Mammography Laser Imaging Film is available in three sizes to fit your mammography imaging needs.
- Long shelf life—DRYVIEW Film can be stored and used for many months, simplifying inventory control and creating a potential for cost savings.
- Simple film reloading—DRYVIEW Film cartridges and Film packs load easily in full light and use minimal packaging.

Exceptional Convenience and Cost Savings

- DRYVIEW DVM+ Mammography Film features preferred Dmax maximum image densities $D_{max} = 4.0$
- Distinct black tone and wide dynamic range, ensures clear, crisp diagnostic images.
- Proven support for CR, DR and FFDM mammography applications.



Product Specifications

DRYVIEW DVM MAMMOGRAPHY LASER IMAGING FILM DRYVIEW DVM+ MAMMOGRAPHY LASER IMAGING FILM

Three film sizes for a range of imagers and applications

Choose from three film sizes on 7-mil polyester base to satisfy your department image size needs.

- 11 x 14 in. (28 x 35 cm.)
- 10 x 12 in. (25 x 30 cm.)
- 8 x 10 in. (20 x 25 cm.)

DRYVIEW Mammography Laser Imaging Film

- Enables higher Dmax images
3.6 Dmax with DVM film
4.0 Dmax DVM+

System-matched to boost productivity

- DRYVIEW Films are system-matched with DRYVIEW Laser Imagers to enable Automatic Image Quality Control (AIQC).
- AIQC calibrates DRYVIEW Systems to optimize quality—and to help ensure that contrast and density meet preset user preferences.
- This quality control is performed with no operator intervention, enhancing productivity.

Storage and handling of film

- Just like other photographic films or data-storage materials, DRYVIEW Film requires reasonable care during storage and handling. Store unexposed film at 39 to 75 °F (4 to 24 °C), at 30 to 50% RH, and properly shielded from x-rays, gamma rays, or other penetrating radiation in order to achieve consistent results up to the expiration date indicated on the film package.
- Tests under ISO (International Standards Organization) processed DRYVIEW film methods indicate DRYVIEW Film is archival for 100+ years when stored at ISO-recommended maximum temperature of 77 °F (25 °C), at 30 to 50% RH—far exceeding requirements for oncology and pediatric applications. Keep processed film in a cool, dry place that is properly shielded from penetrating radiation and chemistry fumes.



www.carestream.com

